

	GBC 212-50	GBC 212-70	GBC 212-90	GBC 224-50	GBC 224-70
Ingangsspanning <i>Input Voltage</i>	180 - 240VAC, 50/60Hz				
Uitgangsspanning Nom. <i>Output voltage Nom.</i>	12VDC			24VDC	
Inschakelspanning <i>Active battery Voltage</i>	≥ 4 Volt			≥ 7 Volt	
Laad karakteristiek <i>Charge curve</i>	IUoUo				
Laadstroom max. <i>Charge current max</i>	50 Amp.	70 Amp.	90 Amp.	50 Amp.	70 Amp.
Lichtnetbelasting max. <i>Lighting load max.</i>	4,55 Amp.	6,35 Amp.	8,0 Amp.	9,10 Amp.	12,75 Amp.
Ideale omgevings-temp. <i>Ideal working temp.</i>	5-20°C				
Beveiligingen <i>Protections</i>	Ompoling, kortsluiting, temperatuur <i>Reverse polarisation, short circuit, temperature</i>				
Luchtvochtigheid max. <i>Relative humidity max.</i>	80%				
Koeling <i>Ventilation</i>	Electronisch gestuurde ventilator <i>Electronically controlled fan</i>				
Batterij aansluiting <i>Battery connection</i>	M8 bouten (messing nikkel) <i>M8 bolts (brass nickel)</i>				
Soft start <i>Soft start</i>	Primair en secundair <i>Primary and secondary</i>				
Galvanisch gescheiden <i>Galvanic separated</i>	Ja Yes				
Behuizing <i>Housing</i>	Geanodiseerd en geëxtrudeerd aluminium <i>Anodized and extruded aluminium</i>				
Beschermingsgraad EMC <i>Level of protection EMC</i>	IP 205				
Afmetingen lxbxh <i>Dimensions lwxhx</i>	250 x 165 x 160mm		350 x 165 x 160mm	275 x 165 x 160mm	350 x 165 x 160mm
Gewicht <i>Weight</i>	13kg		18kg	13kg	18kg

