

	TBC 612-1-15	TBC 612-1-25	TBC 612-1-35	TBC 612-1-50	TBC 624-1-10	TBC 624-1-20	TBC 624-1-30	TBC 624-1-40
Ingangsspanning <i>Input Voltage</i>	230VAC 115VAC			180 - 240VAC, 50/60Hz 95 - 125VAC, 50/60Hz				
Uitgangsspanning (nominaal) <i>Output voltage (nominal)</i>		12VDC			24VDC			
Inschakelspanning <i>Active battery Voltage</i>		≥ 4 Volts			≥ 7 Volts			
Laadkarakteristiek <i>Charge curve</i>				IUoJoe / IUlaJoe				
Max. laadstroom <i>Maximum charge current</i>		15 Amp.	25 Amp.	35 Amp.	50 Amp.	10 Amp.	20 Amp.	30 Amp.
Max. lichtbelasting <i>Max. lighting load</i>	230VAC 115VAC	1,8 Amp. 3,7 Amp.	2,6 Amp. 6,1 Amp.	3,8 Amp. 8,3 Amp.	5,5 Amp. 12,3 Amp.	2,5 Amp. 5,3 Amp.	4,4 Amp. 10 Amp.	6,6 Amp. 14,5 Amp.
Ideale omgevingstemperatuur <i>Ideal working temperature</i>				5-20°C				
Beveiligingen <i>Protections</i>				Ompoling, kortsluiting, temperatuur, ingangsspanning, stroombegrenzing, soft start <i>Reverse polarisation, short circuit, temperature, input voltage, current limitation, soft start</i>				
Max. luchtvochtigheid <i>Max. relative humidity</i>				90%				
Koeling <i>Ventilation</i>				Mechanisch <i>Mechanical</i>				
Batterij aansluiting <i>Battery connection</i>				M6 bouten (messing nikkel) M6 bolts (brass nickel)				
Soft start				Primair en secundair <i>Primary and secondary</i>				
Galvanisch gescheiden <i>Galvanic separated</i>				Ja Yes				
Behuizing <i>Housing</i>				aluminium <i>aluminium</i>				
Beschermingsgraad (EMC) <i>Level of protection (EMC)</i>				IP 647				
Afmetingen (lxbxh in mm) <i>Dimensions (lwxhxh mm)</i>	200x200x110	250x200x110	300x200x110	400x200x110	200x200x110	250x200x110	300x200x110	400x200x110
Gewicht (kg) <i>Weight (kg)</i>	6	9	9	14	7	9	10	16