

	TBC 612-2-15	TBC 612-2-25	TBC 612-2-35	TBC 624-2-10	TBC 624-2-20	TBC 624-2-30
Ingangsspanning <i>Input voltage</i>	180 – 240VAC, 50/60Hz					
Uitgangsspanning nominaal <i>Output voltage nominal</i>	12VDC			24VDC		
Laadspanningen <i>Charge voltages</i>	14,4 / 13,5 VDC			28,8 / 27,0 VDC		
Inschakelspanning <i>Active battery voltage</i>	≥ 4 Volt			≥ 7 Volt		
Laad karakteristiek <i>Charge curve</i>	IUoUoe					
Laadstroom max. <i>Max. charge current</i>	15 Amp	25 Amp	35 Amp	10 Amp	20 Amp	30 Amp
Lichtnetbelasting (bij maximaal vermogen) <i>Lighting load (at max. charge current)</i>	1,3 Amp	2,25 Amp	3,15 Amp	1,8 Amp	3,65 Amp	5,45 Amp
Ideale omgevingstemperatuur <i>Ideal working temperature</i>	5-20°C					
Beveiligingen <i>Protections</i>	Ompoling, kortsluiting, temperatuur, ingangsspanning, stroombegrenzing <i>reverse polarisation, short circuit, temperature, inputvoltage, current</i>					
Max. luchtvochtigheid <i>Max. relative humidity</i>	90%					
Koeling <i>Ventilation</i>	Mechanisch <i>Mechanical</i>					
Batterij aansluiting <i>Battery connection</i>	M6 bouten (messing nikkel) <i>M6 bolts (brass nickel)</i>					
Soft start <i>Soft start</i>	Primair en secundair <i>Primary and secondary</i>					
Galvanisch gescheiden <i>Galvanic seperated</i>	Ja <i>Yes</i>					
Behuizing <i>Housing</i>	Geanodiseerd aluminium <i>Anodized aluminium</i>					
Beschermingsgraad <i>Level of protection</i>	IP 647					
Afmetingen (lxbxh mm) <i>Dimensions (lxbxh mm)</i>	300x200x110					
Gewicht (kg) <i>Weight (kg)</i>	9	9	10	9	10	10